

Alimentations à découpage - PROeco


Type	entrée AC	entrée biphasée AC	entrée DC	sortie	cou-rant	dimensions l x h x p	Cdt	référence
PRO ECO 72W 24V 3A	85...264 VAC		80...370 V DC	22...28 V	3A	34 x 125 x 100	1	1469470000
PRO ECO 120W 24V 5A	85...264 VAC		80...370 V DC	22...28 V	5A	40 x 125 x 100	1	1469480000
PRO ECO 240W 24V 10A	85...264 VAC		80...370 V DC	22...28 V	10A	60 x 125 x 100	1	1469490000
PRO ECO 480W 24V 20A	85...264 VAC		80...370 V DC	22...28 V	20A	100 x 125 x 100	1	1469510000
PRO ECO 960W 24V 40A	85...264 VAC		80...370 V DC	22...28 V	40A	160 x 125 x 120	1	1469520000
PRO ECO3 120W 24V 5A	3 x 320...575 VAC	2 x 360...575 VAC		22...28 V	5A	40 x 125 x 100	1	1469530000
PRO ECO3 240W 24V 10A	3 x 320...575 VAC	2 x 360...575 VAC		22...28 V	10A	60 x 125 x 100	1	1469540000
PRO ECO3 480W 24V 20A	3 x 320...575 VAC	2 x 360...575 VAC		22...28 V	20A	100 x 125 x 100	1	1469550000
PRO ECO3 960W 24V 40A	3 x 320...575 VAC	2 x 360...575 VAC		22...28 V	40A	160 x 125 x 120	1	1469560000
PRO ECO 72W 12V 6A	85...264 VAC		80...370 V DC	10...16 V	6A	34 x 125 x 100	1	1469570000
PRO ECO 120W 12V 10A	85...264 VAC		80...370 V DC	10...16 V	10A	40 x 125 x 100	1	1469580000
PRO ECO 240W 48V 5A	85...264 VAC		80...370 V DC	42...56 V	5A	60 x 125 x 100	1	1469590000
PRO ECO 480W 48V 10A	85...264 VAC		80...370 V DC	42...56 V	10A	100 x 125 x 120	1	1469610000