

HD35ED1TV – HD35EDL1TV Humidity wireless data logger with fixed vertical probe



9bfY[]ghfYi f`XY`XcbbfYg`gUbg`Zi`Xfi a`]X]hf" 5Z]WU[Y`@78`dYfgcbbU`]gf`fi b]ei Ya YbhUj YW`fdh]cb`@`" =`gbcW`Y`Yg`a Ygi fYg`XUbg`gU`a`fa`c]fY`]bhYfbY`f` ,` \$\$\$`fW`Ubh`]`cbgk`Yh`fUbg`a`Yh`Ui`hca`Uh]ei`Ya`Ybh`Yg`XcbbfYg`YbfY[]ghfYg`{`fi`b]hf`XY`VUgYz`{`]bhYfj`U`Yg`ff[i`]Yfg`ci`gi`f`XYa`UbXY"

GcbXY`j`Yfh]W`Y`Zi`Y`{` \i`a`]X]hf`fY`Uhj`Y`Uj`YWW`dhYi`f`F`<"`XY` \Ui`hY`dfW]g]cb.`
5`Ufa`Y`UV`i`gh]ei`Y`Uj`YWGcbbYf]Y`]bhYfbY`" 7`cbZi[i`fU]cb`j`jU`Y`c[]WY`< 8`)`5D!`G`ci`Y`WUj`]Yf`Z`cbUj`fj`Yfg]cb`i`b]ei`Ya`YbhUj`YW@78k`" 5`]a`Ybhf`dUf`U`VU`hYf]Y`]bhYfbY`" =bgU`Uh]cb`a`i`fU`Y`Ua`cj`]Y`Y`f[`fU]XY`Xi`gi`ddcfh`Zci`fb]k`ci`Zi`Y`fUj`YWW`f]XYg`Yb`cdh]cbk`

7UdhYi f	Capacitiz
D`U[Y`XY`a`Ygi`fY	0...100% RH
Resolution	0.1% RH
Df`fW]g]cb` (@ 23 °C)	± 1.5 %RH (0..90 %RH) ± 2 %RH (d`U[Y`fYghUbhYk`
d`U[Y`XY` temperature	-20...+80 °C
8`f]j`Y`Temperature	±2% XY`U`d`U[Y`XY`Z`cbW]cbbYa`Ybh
GHU]j]hf`{`cb[`hYfa`Y	1% / Ub

Transmission frequency`	868 MHz,
DcfhY`Transmission	300 m`Yb`W`Ua`d`]VfY` (dYi`h`..hfY`f`f`Xi`]hdUf`Yg`cVg`UWg
interval`YbfY[]gh`.....`	% 2, 5, 10, 15, 30 s / 1, 2, 5, 10, 15, 30, 60 min
5`]a`YbhU]cb`	Non rechargeable lithium thionil chloride (Li-SOCl ₂) batterY`]bhYfbY, 3.6 V,
8i`fY`XY`j`Y`BatterY`j`	2`Ubg`gUbg`f`f`d`f`hY`f`Uj`YW`]bhYfj`UY`XY`mesurY`XY`5` s`Yhlog`intervalY`XY`30` s)
conditions`Z`cbW]cbbYa`Ybh`	20...+70 °C / 0...85 %RH non condensf
Dimensions	135 x 144 x 33 mm
dc]Xg`.....`	200 g approx.
6c]h]Yf`.....`	ABS
Protection`.....`	IP 64

7cXY`XY`W`a`a`UbXY`

